

Overview of TD/TS family

Susol

TD series	
TD125U	
Frame size	[AF]
Rated current In	[A]
No. of Poles	2, 3
Rated operational voltage, Ue AC	[V]
UL interrupting rating	[kA]
AC 50/60Hz	120V 240 V 480 V 600 V
Reference standard	125 15, 20, 30, 40, 50, 60, 80, 100, 125 600
Trip unit (Thermal-Magnetic)	NU 50 50 35 10
Variable accessories	HU 100 100 65 14
Mechanical life	UL 489
Electrical life @600V AC	-
Weight 3-Pole	
Basic dimension, W x H x D 3-Pole	

Overview of TD/TS family

Susol

TS series



TS250U		TS400U		TS800U	
250		400		800	
150, 160, 175, 200, 225, 250		300, 350, 400		500, 600, 700, 800	
2, 3		2, 3		2, 3	
600		600		600	
NU	HU	NU	HU	NU	HU
50	100	50	100	50	100
35	65	35	65	35	65
10	18	14	20	18	25
UL 489		UL 489		UL 489	
(3Ø)		(3Ø)		(3Ø)	
5,000		5,000		3,000	
1,000		1,000		500	
4.19/1.9		12.57/5.7		29.98/13.6	
4.13 × 7.01 × 3.39 / 1.05 × 1.78 × 0.86		5.51 × 11.50 × 4.33 / 1.40 × 2.92 × 1.10		8.27 × 16.85 × 5.31 / 2.10 × 4.28 × 1.35	